

#Corner originally set as a post in 1820by John Hendricks with the following witnesses: 12" beech bearing south 2 degrees, thence west 26 links, and a 15" dogwood bearing north 32 degrees, thence east 25 links. (M.C. Atlas p. 14) A survey by John Coyner on May 14, 1860 indicates a found stone with the following witnesses: corner of church bearing south 34 degrees, thence east 45 links, and a 18" elm bearing north 9 degrees, thence east 45 links. (Warren Legal Book p. 37) Corner referenced by Wilcoxen on 8/26/77 and called a square bolt at surface with brass plug underneath. Corner referenced by Greene on 1/21/88 and called a brass plug in disc. Corner referenced by Whiteside on 4/16/93 and called a cut x in copperweld. Corner referenced by Kiste on 1/23/97 and called a cut x in copperweld. Corner excavated on 8/12/02 by Wilcoxen and a copperweld with a 3" octagon plate was found 5" down. A # 205 cast iron Harrison monument was set in position as the corner.

	15052206	
REF.	DISTANCE	DESCRIPTION
1.	117.50	Mag nail w/brass washer SE PwP#2-621 GB 24"up
2.	115.95	Mag nail w/brass washer W PwP#23-651 GA 24"up
3.	45.64'	Cotton Gin spindle N 18" mulberry 18"up
4.	134.59'	Cut 'x' top R/W marker